PERFOIL 100 - 150 - 320

Mineral oil for the lubrication of pneumatic equipments

APPLICATION

- For the lubrication of pneumatic drills, burins and other pneumatic or hydraulic tools.

TECHNICAL PERFORMANCE

- Very good EP, anti-wear, rust-proofing and anticorrosive properties.
  Damp-proofing.
  Excellent adhesive properties.
  Exceed 3000 hours in extreme conditions.

SPECIFICATIONS

- The PERFOIL range overlead INGERSOLL RAND, ATLAS COPCO, GARDNER DENVER, JOY (RD01), HOLLMAN, TAMPELA... recommendations.
  For Crawler with a VRD-550 INGERSOLL RAND drillrock.

TYPICAL PROPERTIES

Test	Method	Units	Result		
Grade ISO VG	ISO 3448		100	150	320
Density at 15°C	ASTM D1298	Kg/L	0.890	0.895	0.910
Viscosity at 40°C	ASTM D445	cSt	90-110	132-165	300-350
Viscosity Index	ASTM D2270				95
Flash Point	ASTM D92	°C Mini	220	230	250
Pour point	ASTM D97	°C Max	-25	-20	-10
4 balls test 40Kg-1200rpm-75°c/1H	ASTM D2266	mm	<0.5	<0.5	<0.5
Corrosion on Copper 3H à 100°C	ASTM D130	Max	1b	1b	1b

Characteristics are given as an indication

Head Office : Zone Euro 2000-Rue de la Dame-30 132 Caissargues -France
Tél : +33 (0)4 66 21 22 74 -Fax : +33 (0)4 66 70 64 11
E-mail : mylubricants@mylubricants.com

S.A. au capital de 37 000€ RCS NIMES 504 548 595 00017 - N° TVA FR n°73 504 548 595 NAF 4791B